



Unilong Industry Co., Ltd

Add: No.2000 Shunhua Rd, High-Tech Zone , Jinan City, Shandong Province, China
Contact: +86-18653132120

Product name: 3-Ethyl-3-oxetanemethanol

CAS: 3047-32-3

Molecular weight: 116.16



Item	Standard
Boiling point	96 °C/4 mmHg (lit.)
Density	1.019 g/mL at 25 °C (lit.)
Vapor pressure	3.1Pa at 25 °C
Refractive index	n ₂₀ /D 1.453(lit.)
Flash point	227 °F
LogP	0.6 at 25 °C
Acidity coefficient (pKa)	14.58±0.10(Predicted)



Unilong Industry Co., Ltd

Add: No.2000 Shunhua Rd, High-Tech Zone , Jinan City, Shandong Province, China
Contact: +86-18653132120

Application:

3-Ethyl-3-oxetanemethanol is mainly used in UV polymerization, coatings and resin synthesis. 3-Ethyl-3-oxetanemethanol is a UV-curable monomer material that can be used in UV inks, UV coatings and UV adhesives. 3-Ethyl-3-oxetanemethanol can be used as a raw material for other UV-cured monomers, and its properties and functions are equivalent to OXT-101.

Package:

25kg/drum or according to customer requirements.

Unilong Industry